

FIRE FIGHTING TELEPHONE SYSTEM (UPTO 64Z)

A-FF-TP-2Z



Features:

- Microprocessor based.
- As per IS2189:1999 Fire alarm code of practice.
- Modular Construction.
- Clear labeled all indicating lamp, control switch and user instruction based sticker on Front.
- Soft Touch programmable Function & Control switch.
- Monitor for System ON & Silence.
- Control Switch: Call, Silence and Reset.
- Zone display: Call & Accept.
- 24VDC auxiliary supply for other devices.
- When mains fails auto change over to battery vice-versa.
- PWM based built in charger with auto cutoff.
- In built auto charger and battery housing for 7 Ah x 12V -2 No.
- System ON/OFF switches with protective fuse for AC/DC/Battery.
- Fabrication MS with powder coated ,Top entry cable entry, front operable door.

PARAMETER	VALUE
Plug Diameter	6mm
Alarm	C, No Type
Size	90x90x30mm
Alarm Current	32.5mA
Stand by Current	NIL
Fabrication	Stainless Steel
Operating Voltage	24VDC± 10%



FIRE FIGHTING TELEPHONE SYSTEM (UPTO 64Z)

A-FF-TP-2Z



Specifications:

MODEL	A-FF-TP-2Z (Upto 64Z)
Technology	DTMF
Communication	PSTN Based
Frequency Range	300Hz-3400Hz
Voice Distortion	less than 10%
Operating Current	17mA-31mA
Operating Voltage	24VDC
Plug Diameter	6mm
Material & Color	ABS, Red

MICROPROCESSOR BASED - AVAILABLE IN 2, 4, 6, 8, 16, 32, 64 ZONE.

Functions:



**Floor Calling
Monitoring Facility**



**Floor Call
Accept Facility**



**Duplex Talk
Back Operation**



**Buzzer Silence
Facility with Indication**



**2 Wire 24v Operated
Telephone Circuit**

