

ZONE VOICE ALARM REMOTE MICROPHONE

RM-EVAC-TS-120Z



Specification:-	
Model	RM-EVAC-TS-120Z
Description	Voice Alarm Remote Microphone (Touch Screen)
Power Consumption	3W
Zone Capacity	120 zones
System Capacity	32 Remote Microphone
Line Input	350mV, 10k Ω
Mic Input	5mV, 600 Ω
Frequency Response	80Hz ~ 16kHz
THD	<1% at RMS, 1KHz
S/N Ratio	>70dB
Operating Temp	-20°C to +70°C
Power Supply	DC24V, \pm 20%
Humidity	<95% no condensation
Dimension	256(W) X149(H) X 52(D) mm
Weight	1.5 kg

Features:

- Digital voice evacuation system remote paging microphone.
- Each microphone of 120 zone capacity.
- Support 32 remote microphones of loop connection.
- Remote paging microphone with touch screen display.
- System indicators of AC, DC, fault, Mic status and test.
- 120 zone selection buttons through touch screen and all zone/talk button.
- Two RJ45 ports for connection with EVAC-500 and next remote microphone.
- One 3.5mm line input, with output volume control.
- Support PPT and normal paging two modes.
- DC24V power supply or POE.
- Support loop connection and paging microphone failure has been supervised.
- With free software to monitor the microphone working status and fault.

Rear Panel:

